

CONDUCTIVE FIBER**1. Field of the Invention**

5 The present invention relates to a conductive fiber. More particularly, the present invention relates to a flexible, conductive silicon fiber for use with wearable electronic and sensor devices making contact with the skin.

2. Description of the Prior Art

10 The use of conductive fibers in various sewn or woven fabrics used as conductive traces, bio-sensors, electrodes, and other wearable electronic devices is well known. It is also commonly known to incorporate conductive silicon into these different fabrics to prevent the conductive fibers, which
15 typically include at least some metal, from making direct contact with the skin. The use of silicon provides flexibility and helps to eliminate the negative effects associated with metal directly contacting the skin. A drawback of silicon, however, is that it tends to become slippery when exposed to moisture (e.g.
20 perspiration). Thus, there is a need for a conductive fiber having the beneficial properties of conductive silicon without the above noted drawback. The preferred embodiments of the present invention fulfill this need.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved conductive fiber for direct contact with skin.

It is another object of the present invention to provide
5 such a conductive fiber configured for prolonged contact with skin.

It is still another object of the present invention to provide such a conductive fiber capable of being woven, knitted, and/or sewn by conventional methods.

10 It is yet another object of the present invention to provide such a conductive fiber adapted for use with various wearable electronic devices and/or sensors.

It is a further object of the present invention to provide such a conductive fiber adapted for use with various textile
15 elements including electrical instruments such as medical instruments, electrodes and sensors.

It is still a further object of the present invention to provide such a conductive fiber that enhances comfort and reduces the negative side effects derived from long-term contact with the
20 skin.

These and other objects and advantages of the present invention are achieved by a first preferred embodiment of the conductive fiber of the present invention. The conductive fiber comprising a fiber mesh or construction preferably having one or

more non-slip fibers and one or more conductive fibers intertwined with the one or more non-slip fibers. These non-slip and conductive fibers are intertwined using any known conventional method for weaving, sewing or knitting. Preferably, 5 the one or more conductive fibers have a conductive threadlike core enclosed by a conductive semi-fluid sleeve.

The objects and advantages of the present invention may also be achieved by a second preferred embodiment of the conductive fiber of the present invention. This conductive fiber has a 10 conductive threadlike core with an outer layer of at least two different fibers. The at least two different fibers include at least one non-slip fiber and at least one semi-fluid conductive fiber. Preferably, the conductive fiber can be sewn, woven or knitted using conventional methods to form a conductive fiber 15 mesh or construction.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is more fully understood by reference to the following detailed description of a preferred embodiment 20 in combination with the drawings identified below.

Fig. 1 is a plan view of a fiber mesh or construction in accordance with a first preferred embodiment of the present invention;

Fig. 2 is a longitudinal section view of a first conductive

fiber of the fiber mesh of the preferred embodiment of Fig. 1;
and

Fig. 3 is a plan view of a second conductive fiber in
accordance with a second preferred embodiment of the present
5 invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring to the drawings and, in particular, Fig. 1, there
is shown an improved fiber mesh or construction in accordance with
10 a first preferred embodiment of the present invention generally
represented by reference numeral 1. Preferably, fiber
construction 1 has one or more non-slip fibers 5 and one or more
conductive fibers 10. The one or more conductive fibers 5 are
intertwined with the one or more non-slip fibers using any known
15 conventional method for weaving, sewing or knitting.

Each non-slip fiber 5 preferably has properties that
facilitate comfortable engagement with the skin. For example, a
rubber extruded fiber may be used. Non-slip fibers 5 preferably
can also have different shapes or sizes such that fiber
20 construction 1 can have different adaptations to accommodate
different uses.

Referring to Fig. 2, each conductive fiber 10 has a
conductive threadlike or fiber core 15 enclosed by a conductive
semi-fluid sleeve 20. Preferably, core 15 and sleeve 20 are

configured to engage securely together. Sleeve 20 is preferably connected to core 15 via sonic welding. However, other connecting methods may also be used.

Preferably, each conductive fiber 10 has a high tensile strength and a weight and consistency of a material that provides a high degree of flexibility during manufacture and wear. Each conductive fiber 10 preferably also facilitates electrical communication between an electrical power source (not shown) and fiber construction 1. A connector (not shown) preferably provides a medium for the electrical communication between the electrical power source and fiber construction 1. The connector can have any configuration suitable to provide the means or way for this electrical communication. Conductive fibers 10, similar to non-slip fibers 5, can preferably also have different shapes or sizes such that fiber construction 1 can have different adaptations to accommodate different uses.

Core 15 can preferably have different conductivities. Core 15 can be made of any suitable conductive material, including for example, a metalized foil, a conductive polymer, or a graphitized or metalized fiber or yarn.

Sleeve 20 is preferably made of an electrically conductive silicon gel. However, any material having a similar conductivity and viscosity to that of silicon gel may also be used. The viscosity of sleeve 20 preferably facilitates adhesion to core 15. Sleeve 20 facilitates electrical communication between conductive fiber 10 and the skin. This electrical communication

preferably facilitates performing various operations. For example, such operations include providing selective electronic massage therapy, selectively collecting and recording electronic data, and/or providing selective electrical stimulation.

5 Thus, fiber construction 1 forms a conductive fabric preferably configured for use with various wearable electronic devices and/or sensors that make direct contact with the skin. Preferably, conductive fibers 10 can be woven into a multitude of different patterns facilitate different applications in use.

10 Referring to Fig. 3, there is shown a conductive fiber in accordance with a second preferred embodiment of the present invention generally represented by reference numeral 30. Preferably, conductive fiber 30 has a conductive threadlike or fiber core 35 with an outer layer 40. Outer layer 40 has at
15 least one non-slip fiber 45 and at least one semi-fluid conductive fiber 50 securely wrapped about fiber core 35. Preferably, conductive fiber 30 can be sewn, woven, or knitted using conventional methods into a conductive non-slip fiber mesh or fabric. Preferably, conductive fiber 30 is suitable to be
20 woven into a multitude of different patterns in order to facilitate different applications in use.

Fiber core 35 can preferably have different conductivities.

Fiber core 35 can be made of any suitable conductive material, including for example, a metalized foil, a conductive polymer, or
25 a graphitized or metalized fiber or yarn. Fiber core 35 preferably facilitates electrical communication between an

electrical power source (not shown) and semi-fluid conductive fiber 50.

Non-slip fiber 45 of outer layer 40 has properties that facilitate comfortable engagement with the skin. For example, a
5 rubber extruded fiber may be used. Non-slip fiber 45 can also have different shapes or sizes such that conductive fiber 30 can have different adaptations to accommodate different uses.

Semi-fluid conductive fiber 50 of outer layer 40 is preferably made of an electrically conductive silicon gel.
10 However, any material having a similar conductivity and viscosity to that of silicon gel may also be used. The viscosity of semi-fluid conductive fiber 50 preferably facilitates adhesion to fiber core 35. Also, semi-fluid conductive fiber 50 preferably facilitates comfortable electrical communication between
15 conductive fiber 30 and the skin.

Thus, conductive fiber 30 can be used to create a conductive non-slip fabric that can preferably be used in conjunction with a variety of electrical mechanisms. For example, such mechanisms include wearable devices or sensors, medical instruments, and
20 different health and fitness therapy devices. This conductive non-slip fabric, similar to fiber construction 1, can preferably be any desired shape, size or configuration necessary to perform a desired function.

The present invention having been thus described with
25 particular reference to the preferred forms thereof, it will be

obvious that various changes and modifications may be made therein without departing from the spirit and scope of the present invention as defined herein.